

CERTIFICATE OF COMPLIANCE

Certificate Number E514431
Report Reference E514431-20201028
Date 2020-November-12

Issued to: SIA TRADING SAC
CALLE LAS FRESAS MZA " J " – LOTE 15A
Lima PE

This is to certify that representative samples of CABLE TRAYS, METAL
See Addendum Page for Product Designation(s).

Have been investigated by UL in accordance with the Standard(s) indicated on this Certificate.

Standard(s) for Safety: Sections 392.60(A) and 392.60(B) of NFPA 70, National Electrical Code
NEMA VE 1, Metal Cable Tray Systems

Additional Information: See the UL Online Certifications Directory at <https://iq.ulprospector.com> for additional information

This Certificate of Compliance does not provide authorization to apply the UL Mark. Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number E514431
Report Reference E514431-20201028
Date 2020-November-12

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements


Products Covered:

Ladder cable trays BTE Series: BT followed by E, followed by CS or CR, followed by GC or PG, followed by (ES) 1.5, 2.0, 2.5, or 3.0, followed by (W) which may be any value from 100 to 900 followed by (H) which may be 50, 100, or 150, followed by (L) which may be any value from 2.4 to 6 followed by ST.

Ladder cable tray Accessories: One of the following 2 or 3 letters: "HC" (Horizontal curve), "CVE" (Vertical external curve), "CVI" (Vertical internal curve), "HA" (Articulated horizontal curve), "VA" (Articulated Vertical curve), "TH" (Horizontal Tee), "TV" (Vertical Tee), "CZH" (Horizontal cross), "RC" (Central reduction), "RD" (Right reduction), "RI" (Left reduction), "YH" (Horizontal Yee), followed by E, followed by CS, followed by GC or PG, followed by (ES) which may be 1.5, 2.0, 2.5, or 3.0, followed by (W) which may be any value from 100 to 900 followed by (H) which may be 50, 100, or 150, may be followed by (R) which may be 150, 300, 600, or 900, may be followed by (O) which may be 30, 45, 60, or 90, Followed by ST.

Ladder cable tray Covers TR or T2A Series: TR or T2A followed by CS, followed by GC or PG, followed by 1.5, followed by (W) which may be any value from 100 to 900 followed by (L) which may be any value from 2.4 to 6.

Ladder cable tray accessory Covers TR or T2A Series: TR or T2A followed by CS, followed by GC or PG, followed by 1.5, followed by (W) which may be any value from 100 to 900



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

